Triple-S Chemical Products, Inc.



3464 Union Pacific Avenue Los Angeles, CA 90023 www.concrete-stains.com Toll Free (888) 417-5214

Tel: (323) 261-7301

Fax: (323) 261-5567

WSL-45 Clear Water Based Sealer

DESCRIPTION:

WSL-45 is a clear, water born, air drying, clear lacquer, which is recommended for use on all types of concretes, bricks, marbles, etc. WSL-45 dries to a crystal clear finish providing a penetrating seal coat over concrete or brick. WSL-45 comes in a glossy or flat finish.

ADVANTAGES:

- 1. Non-flammable, very safe.
- 2. Excellent corrosion and tarnish protection.
- 3. Excellent adhesion.
- 4. Excellent solvent resistance and humidity resistance.
- 5. Good to excellent stain resistance.
- 6 Good to excellent hardness

Operating Conditions:

- Remove any paint, wax, dust or oil from the concrete. Rinse thoroughly with water and allow it to dry.
- WSL-45 (Glossy or Flat) is supplied ready to use. Best application method is with a rayon or microfiber mop. Simply drag mop across floor with adequate amounts of WSL-45. Apply also with a sponge, roller, brush or spray, using conventional air and airless spray equipment.
- Use a roller to remove excess sealer.
- A second coat can be applied if so desired should be applied once the first layer has dried, typically within 6 hours of applications.

Safety Precautions: Avoid contact with skin, use rubber gloves when handling. Do not take internally. Keep away from children!

Packaging: Available in 1 gallon, 5 gallons or 55 gallons.

TYPICAL PROPERTIES

Appearance: Milky white emulsion

Total solids, by weight: 25% pH: 8.0 Non-volatile%: 75%

Freeze/thaw stability: Keep from freezing

Heat stability, one month, 52 °C:

Mechanical Stability:

Volatile organic compounds:

Suggested dry film thickness:

O.K.

Excellent

Less than 250

1 mil to 2 mil

CHEMICAL RESISTANCE

	A	В	C
Water	10	10	10
Brake fluid	1	1	1
Transmission fluid	9	10	10
Gasoline	3	10	10
Ethanol 50%	2	10	10
Isopropanol	4	10	10
Ethylene glycol	10	10	10

C= Whitening